

Weisscam HS-2

The WEISSCAM HS-2 highspeed camera offers you brilliant slow motion quality with up to 4.000 frames in HD. The interchangeable mount system makes the camera one of the most versatile highspeed systems in the world - by maintaining low pricing rates, starting at € 1.199,-. Get in touch to learn more!

Technical Data

Frame Rates	4.000 fps @ 720p 2.000 fps @ 1080p 1.500 fps @ 2K
Maximum Framerate	72.275 fps @ 100×100 Pixels
Signal	RAW Signal: 12 bit uncompressed WEISSCAM RAW HD Signal: 10 bit YCbCr 4:2:2
Signal Output	1280 x 720p: 50p 1920 x 1080: 23,98psf, 24psf, 25psf, 29,97psf, 30psf 1920 x 1080 Dual Link: 50p, 59,94p, 60p 2K: 25p (1920 x 1080 preview)
Sensor	Single CMOS (22,18 x 22,18 mm)
Shutter	Global Shutter
Mount	Interchangeable Mount System (PL, Panavision, BNC-R, Professional, Nikon F, Canon EF, Canon FD, Leica-R, Leica-M)
Recording Time	8 min on 16GB Nano Flash CF (mxf) for HD 20 min on 256GB Gemini SSD (DPX) for WEISSCAM RAW

